ELabELN | Template Use Case White Paper

Western Blot Experiment Template

Structured Documentation for Chemiluminescent Protein Detection — From Cell Lysis Through ECL Image Capture

APPLIES TO

- Academic and life sciences research laboratories
- Biotechnology and pharmaceutical R&D groups
- Contract research organizations (CROs)
- Diagnostic and translational development labs

RELEVANT COMPLIANCE FRAMEWORKS

- FDA 21 CFR Part 11 — Electronic records and signatures
- EU Annex 11 — Computerized systems in regulated environments
- GAMP 5 — Software validation for regulated industries
- NIH / NSF reproducibility and data-management requirements

LabLynx, Inc.
3350 Riverwood Pkwy SE, Suite 1900, Atlanta, GA 30339
866.522.5969 | elabeln.com | info@lablynx.com

 © 2026 LabLynx, Inc. — Public information

1. Executive Summary

The Western blot remains one of the most widely performed techniques in molecular and cell biology — the standard method for confirming that a protein is present, estimating its molecular weight, and comparing its relative abundance between conditions. It is also one of the most documentation-intensive. A single blot threads together a cell line, a lysate, a protein quantification, a gel, a transfer, a blocking step, a primary/secondary antibody pair with specific dilutions and lot numbers, an imaging run, and a densitometry analysis. When that chain is recorded across a paper notebook, a sticky note on the imager, and an unlabeled spreadsheet, the result is the single most common source of irreproducible Western blot data: a band whose provenance cannot be reconstructed.

The ELabELN Western Blot Experiment Template solves this by providing a pre-built, fully structured experiment record that loads from the template library in a single click. It ships with a 10-step protocol covering cell lysis through final image capture, structured and typed fields for gel percentage, loading amount, and transfer and detection parameters, antibody references pre-wired to the ELabELN inventory, and a lane-assignment table configured for a HeLa versus SK-BR-3 reference comparison at HER2 with GAPDH as the loading control. Every step check-off is timestamped to a tamper-evident audit trail, and every electronic signature is captured in a format designed to support FDA 21 CFR Part 11 review.

This white paper describes what the template contains, the experimental use case it is designed to support, the upstream and downstream workflows it connects to, the specific benefits it delivers to the scientist at the bench, and how a laboratory can deploy it and begin running blots within days.

> **KEY BENEFIT**
> Labs that adopt the Western Blot template eliminate manual transcription of antibody lots and dilutions, gain instant cross-blot searchability on sample and target metadata, and produce an audit-ready record with band quantification already normalized to the loading control — without any additional post-run documentation effort.

 © 2026 LabLynx, Inc. — Public information

2. What Is a Western Blot, and Why Does Documentation Matter?

2.1 The Technique

A Western blot (immunoblot) separates proteins from a complex lysate by size using SDS-PAGE gel electrophoresis, transfers the separated proteins onto a membrane, and then detects a specific target with an antibody. A primary antibody binds the protein of interest; an enzyme-conjugated secondary antibody binds the primary; and a chemiluminescent (ECL) or fluorescent substrate produces a signal that is captured as a banding image. The position of the band reports apparent molecular weight, and its intensity — measured by densitometry and normalized to a loading-control protein such as GAPDH — reports relative abundance.

Western blotting is the workhorse method for protein-level confirmation of differential expression, validation of antibody specificity, verification of knockdown or knockout, pathway and post-translational-modification analysis, and routine target quantification. It is frequently the confirmatory step that follows a transcript-level result: a change in expression detected by qPCR is confirmed at the protein level by Western blot before it is reported.

The same sensitivity that makes the technique powerful makes it unforgiving to document. A result can shift entirely with a different antibody lot, a 1:500 versus 1:1000 dilution, a 10% versus 12% gel, a semi-dry versus wet transfer, or a milk versus BSA block. **Each of those variables must be captured if the blot is to be reproducible or defensible.**

2.2 The Documentation Problem

Recording a Western blot in a paper notebook or an ad-hoc spreadsheet creates a set of interconnected, well-known risks:

- Antibody lot numbers, catalog references, and validation status are recorded inconsistently — or not at all — so a result cannot be tied to the exact reagent that produced it.
- Dilutions, gel percentage, loading amount, and transfer parameters live in free text, where they cannot be queried or compared across blots.
- The blot is disconnected from the upstream lysate-preparation record, breaking traceability back to the sample and protein quantification.
- Band intensities are transcribed by hand from imaging software into a spreadsheet, introducing transcription errors and losing the link to the image.
- There is no timestamped, attributed record of who performed each step and when — a baseline requirement for both reproducibility and regulated work.
- Prior blots cannot be found by sample, target, or antibody without manually leafing through notebooks.

These are precisely the gaps that drive Western blot irreproducibility, and they are the gaps this template was designed to close.

 © 2026 LabLynx, Inc. — Public information

3. Template Overview: What Ships with the Template

The ELabELN Western Blot Experiment Template is a pre-populated experiment record available to all ELabELN subscribers directly from the template library. It ships configured for chemiluminescent (ECL) detection on standard imaging systems, with a 10-step protocol running from cell lysis through final image capture. The default configuration assumes RIPA-based lysis with protease inhibitors, BCA protein quantification, 10% SDS-PAGE, semi-dry transfer to PVDF, 5% milk blocking, overnight primary antibody incubation at 4 °C, HRP-conjugated secondary detection, and ECL imaging. Every section is editable — the configuration is a tested baseline, not a locked format.

3.1 Template Sections at a Glance

The template populates the existing ELabELN experiment sections your lab already works in. Your team edits a working baseline instead of building the scaffold from scratch for every blot.

Section	What it pre-populates
Main Text	Protocol summary, antibody validation notes, and expected band sizes, authored in the TinyMCE rich-text editor and linked to the upstream lysate-prep record.
Extra Fields	Structured, typed metadata fields grouped as Sample, Gel & Loading, and Transfer & Detection — cell line, lysate concentration, gel percentage, micrograms per lane, primary and secondary antibody dilutions, transfer method, and blocking agent. Typed values are queryable across every blot in the system.
Steps	A 10-step workflow checklist covering lysis, quantification, gel, transfer, blocking, antibody incubation, and ECL detection. Each tick is timestamped to the audit trail; the imager run is auto-logged.
Compounds	Anti-HER2 and anti-GAPDH primary antibodies, HRP-conjugated secondaries, RIPA lysis buffer, and ECL substrate, pre-linked from the compound database with lot numbers and validation status carried in automatically.
Links & Resources	Pre-wired to the lab's Western Blot SOP v2.4, the HER2 and GAPDH antibody database entries, and the upstream lysate experiment.
Storage & Files	−20 °C antibody aliquot slots and lysate storage references, plus labelled attachment slots for the gel image (TIF) and densitometry data (XLSX).


Main Text
Protocol summary, antibody validation notes, and expected band sizes.
Extra Fields
Typed metadata: cell line, gel %, µg/lane, antibody dilutions.
Steps
10-step checklist; each tick timestamped to the audit trail.
Compounds
Antibodies, RIPA, ECL substrate linked from inventory with lots.
Links & Resources
Western Blot SOP v2.4, antibody entries, upstream lysate prep.
Storage & Files
−20 °C antibody slots; gel image (TIF) + densitometry (XLSX).

Figure 1. The six ELabELN experiment sections pre-populated by the Western Blot template.

3.2 The 10-Step Protocol

 © 2026 LabLynx, Inc. — Public information

The workflow checklist is the operational spine of the template. Each step maps to a discrete bench action and writes a timestamped, user-attributed entry to the audit trail when it is checked off — turning the act of running the blot into the act of documenting it.

Step	Action	What it captures
1	Cell lysis	RIPA buffer + protease inhibitors; lysate ID and storage reference
2	Protein quantification	BCA assay result; lysate concentration field
3	Sample prep & loading	Micrograms per lane; lane assignments
4	SDS-PAGE	Gel percentage; run conditions
5	Transfer	Semi-dry transfer to PVDF; transfer method field
6	Blocking	5% milk (or BSA); blocking agent field
7	Primary antibody	Overnight, 4 °C; antibody link, lot, dilution
8	Secondary antibody	HRP-conjugated; antibody link, lot, dilution
9	ECL detection	Substrate; imager run auto-logged
10	Image capture & analysis	Gel image (TIF) + densitometry (XLSX) attached



Figure 2. The 10-step Western blot workflow — every check-off writes a timestamped entry to the ELabELN audit trail.

 © 2026 LabLynx, Inc. — Public information

4. The Use Case: When and How the Template Is Used

The template is intended as a tested baseline for academic and life sciences labs performing protein-level work. It is configured around a single, recognizable reference experiment — a HeLa versus SK-BR-3 comparison probing HER2 (185 kDa) with GAPDH (37 kDa) as the loading control — but the scenarios it serves are broad.

4.1 Protein-Level Confirmation of a Differential-Expression Result

The most common use case is confirming, at the protein level, a change first observed in transcript data. A lab that detects HER2 over-expression in SK-BR-3 relative to HeLa by qPCR runs this template to confirm the result on protein. Because the ELabELN qPCR template and this Western Blot template share the same HER2/GAPDH, HeLa/SK-BR-3 reference design, the two records link directly: the transcript result and its protein confirmation live in the same searchable system, traceable to one another.

4.2 Antibody Validation and Knockdown / Knockout Verification

Labs validating a new antibody lot, or verifying that an siRNA or CRISPR perturbation reduced the target protein, need a record that ties the band to the exact antibody, dilution, and lysate used. The template's antibody links and typed dilution fields make that record automatic, and the validation-status flag carried from inventory surfaces inline so an unvalidated lot is visible before the run, not after.

4.3 Pathway and Post-Translational-Modification Analysis

For signaling studies — phospho-specific blots, pathway activation timecourses — the structured fields and lane table extend naturally to multiple targets, treatments, and timepoints. The queryable metadata lets a lab retrieve every blot run against a given target or treatment across months of work without reopening individual records.

4.4 Translational and Biomarker Work

Translational teams blotting patient-derived material need the molecular result connected to sample metadata and signed off for studies approaching regulatory submission. The template's inventory links provide the traceability layer, and the electronic-signature step provides the authenticated sign-off.

4.5 Multi-PI, Multi-Lab, and CRO Settings

Because every ELabELN edition includes unlimited users, the PI, postdocs, graduate students, rotating researchers, and visiting collaborators can all run from the same template with no per-seat charge. Granular permissions let the PI decide who may edit blots versus only review them, and the pre-wired SOP link enforces a single, consistent procedure across everyone who uses it — the foundation a CRO needs to standardize documentation across client studies.

 © 2026 LabLynx, Inc. — Public information

5. Dependencies and Connected Workflows

The Western Blot template does not exist in isolation. It sits inside a network of connected laboratory workflows — some upstream, some parallel, some downstream — that give the blot record its full scientific and regulatory value.



Figure 3. The template connects upstream lysate preparation, parallel inventory and SOP systems, and downstream densitometry, analytics, and reporting workflows.

5.1 Upstream: Sample and Lysate Preparation

A Western blot measures protein from a lysate. The template ships with a pre-wired link to the upstream lysate-preparation experiment, so that opening the blot record surfaces the cell line and passage, the lysis conditions and protein quantification (BCA) result, the lysate stock identifier and storage location, and the operator and timestamp of the prep. The blot result is therefore traceable back to the sample without any manual cross-referencing.

5.2 Parallel: Inventory, Antibody, and Reagent Management

The Compounds section links the primary and secondary antibodies, RIPA buffer, and ECL substrate directly to the ELabELN inventory. This is the dependency that matters most for a Western blot, because antibody provenance is the single most common reproducibility failure. Through the link, the record automatically carries:

- **Lot numbers and catalog references** for every antibody, so a result is permanently tied to the exact reagent that produced it.
- **Validation status**, shown inline, so an unvalidated or expired antibody is flagged before the run.
- **Stock levels and low-stock warnings**, so a blot is not started against an aliquot that will run out mid-experiment.

Barcode and QR scanning can populate these links by scanning the physical antibody vial, and expiry alerts prevent use of out-of-date reagents.

5.3 Parallel: SOPs and Protocol Version Control

 © 2026 LabLynx, Inc. — Public information

The Links section connects the blot to the lab's Western Blot SOP (v2.4 in the default configuration). Because the SOP is version-controlled in ELabELN, every blot records which procedure version it followed — so when the method is revised, prior blots remain correctly attributed to the version under which they were run. Template steps can additionally be locked to enforce a validated procedure that bench users can check off but cannot alter.

5.4 Downstream: Densitometry, Analytics, and Reporting

After imaging, the spreadsheet editor captures per-lane band intensity — raw and normalized to the loading control — with fold-change calculated automatically. Densitometry exports from ImageJ, Image Lab, or Empiria Studio can be pasted directly, and the resulting values are typed and queryable across blots for cross-experiment comparison. From there the structured record feeds reporting (publication-ready figures and PDF/ZIP export for audit), the searchable experiment index, and electronic sign-off.

5.5 The ELabELN Suite: Instruments and Dashboards

Everything above is available in ELabELN Standard. Labs on the ELabELN Suite gain three additional layers that connect to the same blot record: LabVia, the instrument layer, captures data directly from imaging systems and other equipment through hundreds of instrument profiles; LabDrive, the data layer, adds metadata search, versioning, and role-based access across all lab files including raw gel images; and LabVista, the analytics layer, builds dashboards, trends, and alerts on top of the structured blot metadata. The same audit trail and data-integrity controls span all layers.

 © 2026 LabLynx, Inc. — Public information

6. How the Scientist Benefits

The template is built to deliver value at the bench, not just to the quality system. The benefits compound with every blot a lab runs.

6.1 Start From a Tested Baseline, Not a Blank Page

The scaffold — protocol, fields, lane table, antibody links — is already built. The scientist edits a working configuration to match the antibody pair they actually run, rather than rebuilding the structure for every experiment. The first blot is faster, and every subsequent one is consistent with it.

6.2 Document by Doing

Checking off each of the 10 steps as it is performed produces a contemporaneous, timestamped record as a by-product of running the experiment. There is no separate write-up phase, and nothing to reconstruct from memory the next morning.

6.3 Never Lose Antibody Provenance Again

Because the antibodies are linked to inventory, the lot number, catalog reference, and validation status are captured automatically and permanently. When a blot needs to be repeated or defended months later, the exact reagent is on the record — the most common Western blot reproducibility gap is closed by default.

6.4 Find and Compare Past Blots Instantly

Typed fields make every blot queryable. A scientist can retrieve every blot run against a target, on a cell line, or with a given antibody dilution in seconds — and compare normalized band intensities across them — instead of leafing through notebooks.

6.5 Produce Audit-Ready Records Without Extra Effort

The tamper-evident audit trail, version-controlled SOP linkage, and electronic signatures mean the record that results from normal use is already structured to support reproducibility documentation, multi-PI collaboration, grant data-management requirements, and FDA 21 CFR Part 11 review when the lab's quality system requires it.

> **AT THE BENCH, IN PRACTICE**
> A graduate student opens the template, swaps the antibody pair and dilutions to match today's run, scans the antibody vials to pull lot numbers, checks off each step as the blot proceeds, pastes the densitometry export, and requests the PI's electronic sign-off. Total added documentation time beyond simply doing the experiment: effectively zero — and the resulting record is searchable, traceable, and audit-ready.

 © 2026 LabLynx, Inc. — Public information

7. The Reference Comparison and Band Quantification

7.1 Default Lane Layout

The lane-assignment table ships configured for technical triplicates of HeLa and SK-BR-3 lysates, probed for HER2 (185 kDa) as the target and GAPDH (37 kDa) as the loading control. This is a recognizable, biologically meaningful reference — HER2 is over-expressed in SK-BR-3 relative to HeLa — that demonstrates the full workflow out of the box. Swap the cell lines, change the target, add treatments or timepoints, or restructure the lanes entirely, then attach the updated layout to the record.



Figure 4. The template's default lane layout — HeLa vs SK-BR-3 technical triplicates, probing HER2 (185 kDa) against a GAPDH (37 kDa) loading control. Illustrative banding shown.

7.2 How the Template Handles Quantification

The spreadsheet editor captures per-lane band intensity, both raw and normalized to the loading control, with fold-change calculated automatically. Densitometry exports from ImageJ, Image Lab, or Empiria Studio paste directly into the editor. Because the values are typed, they are queryable across blots — enabling cross-experiment comparison that a standalone spreadsheet cannot provide. The gel image (TIF) and the densitometry data (XLSX) attach to the same record, keeping the image and its quantification together.

Element	Default configuration	Editable to
Target protein	HER2 (185 kDa)	Any protein target
Loading control	GAPDH (37 kDa)	β-actin, tubulin, vinculin, etc.
Cell lines	HeLa vs SK-BR-3	Any sample or patient-derived material
Replicates	Technical triplicates	Any layout
Detection	ECL chemiluminescence	Fluorescent (IRDye secondaries)

Figure 5. The template's default reference design — fully editable for any blot configuration.

 © 2026 LabLynx, Inc. — Public information

8. Configuring the Template for Your Blot

Adapting the template to a different blot is a matter of editing the relevant sections — not rebuilding the structure.

8.1 Swap the Antibody Pair

Replace the anti-HER2 entry in the Compounds section with your target antibody and the anti-GAPDH entry with your chosen loading control. If the antibodies already exist in the ELabELN compound database, simply re-link them; their lot numbers and validation status flow in automatically.

8.2 Adjust Gel, Loading, and Transfer Parameters

The Gel & Loading and Transfer & Detection fields are typed inputs. Edit the gel percentage, micrograms per lane, antibody dilutions, transfer method, and blocking agent to match your optimized protocol.

8.3 Switch to Fluorescent Detection

The protocol ships for ECL chemiluminescence on standard imaging systems (ChemiDoc, LI-COR Odyssey, iBright, Azure). For fluorescent detection, swap the secondary antibodies to IRDye conjugates and adjust the detection field. For instruments with a different export format, the ELabELN team can map the export as part of onboarding.

8.4 Save a Custom Version

Once configured, save your edits as a private template scoped to your lab, or publish back to the ELabELN template library. Every subsequent run of that blot opens from your configured version, and separate versions can be maintained for different antibody pairs, instruments, or regulatory contexts.

9. Getting Started

ELabELN Standard is a cloud-hosted SaaS deployment typically live within one to two business days of account creation. There is no hardware to buy, no IT project, and no per-seat licensing.

1. **Start an ELabELN account.** Visit elabeln.com/get-started. ELabELN Standard runs on LabLynx's managed cloud infrastructure.
2. **Provision your instance.** LabLynx provisions the instance within one to two business days; you receive a URL, admin credentials, and onboarding documentation.
3. **Load the Western Blot template.** From the template library, select the Western Blot template and click “Use This Template.” An editable instance opens immediately.
4. **Add your antibodies and reagents to the compound database.** Enter your primary and secondary antibodies, RIPA buffer, and ECL substrate with lot numbers and storage locations. This is a one-time setup step.

 © 2026 LabLynx, Inc. — Public information

5. **Link your SOP.** Upload your Western blot SOP and connect it to the template's Links section.
6. **Customize the template for your blot.** Edit the antibody pair, dilutions, gel percentage, transfer method, and lane layout, then save as a private team version.
7. **Run your first blot.** Open your saved template, complete the 10-step checklist, attach the gel image and densitometry data, and have the PI sign off electronically.

TYPICAL TIMELINE

Day 1: Account requested at elabeln.com/get-started. Day 2–3: Instance provisioned; antibody/compound database populated; SOP uploaded. Day 3–4: Template configured and saved as a private version for your blot. Day 4–5: First live blot documented in ELabELN with audit trail and e-signature.

9.1 ELabELN Standard vs. ELabELN Suite

Capability	Standard	Suite
Western Blot template access	Included	Included
Unlimited users	Included	Included
Audit trail and e-signatures	Included	Included
Antibody / compound database with lot tracking	Included	Included
SOP linking and version control	Included	Included
LabDrive file metadata search & versioning	—	Suite layer
LabVia direct imaging-instrument capture	—	Suite layer
LabVista dashboards and analytics	—	Suite layer

 © 2026 LabLynx, Inc. — Public information

10. Frequently Asked Questions

Can I configure the template for my antibody pair?

Yes. Every section is editable. Swap in different primary antibodies, adjust dilutions, change the gel percentage or transfer method, or rearrange the lane layout. Save your edits as a private template scoped to your lab, or publish back to the ELabELN template library. The HER2/GAPDH configuration is the pre-populated example, not a restriction.

Does the template work with my imaging system?

The protocol is written for ECL chemiluminescence on standard imaging systems such as ChemiDoc, LI-COR Odyssey, iBright, and Azure. Fluorescent detection is supported by swapping the secondary antibodies to IRDye conjugates and adjusting the detection field. For instruments that use a different file format, the ELabELN team can map the export as part of onboarding, and the LabVia layer (Suite) supports direct capture from hundreds of instrument profiles.

How does the template handle band quantification?

The spreadsheet editor captures per-lane band intensity — raw and normalized to the loading control — with fold-change calculated automatically. Densitometry exports from ImageJ, Image Lab, or Empiria Studio can be pasted directly, and the values are queryable across blots for cross-experiment comparison.

Is it included in every ELabELN plan?

Yes. Every published template in the ELabELN library is available to all subscribers in both the Standard and Suite editions, with unlimited users in either edition and no per-template fee.

Can my whole lab use this template?

Yes. Every edition includes unlimited users, so the PI, postdocs, graduate students, rotating researchers, and visiting collaborators can all use it without per-seat charges. Granular permissions let the PI control who can edit blots versus only review them.

How quickly can my lab start running blots in ELabELN?

ELabELN Standard cloud deployment is typically live in one to two business days. Once the instance is provisioned, the template loads from the library in a single click, with the antibody references and SOP editable to match the proteins your lab actually runs.

Can I use this template for a regulated study?

ELabELN is designed to support FDA 21 CFR Part 11 compliance. The audit trail, electronic signatures, and tamper-evident record storage the template leverages are engineered to that standard. For studies that require a formal validation package (IQ/OQ/PQ), LabLynx provides a complete validation manual and can support the validation engagement.

 © 2026 LabLynx, Inc. — Public information

11. Conclusion

The ELabELN Western Blot Experiment Template is not simply a digital version of a paper protocol sheet. It is a structured, audit-ready, searchable experimental record that connects to your antibody inventory, your SOPs, your upstream lysate preparation, and — in the Suite edition — your imaging instruments and analytics dashboards. It turns the most provenance-sensitive technique in the lab into a workflow that is faster to execute, easier to review, and built to survive a regulatory audit or a grant replication request.

For a laboratory that runs blots regularly, the benefit compounds quickly. Every blot produces a record that future researchers can find, understand, and build on without reconstruction. Every antibody lot is traceable. Every protocol version is documented. Every step is timestamped. Every sign-off is authenticated. And the most common cause of Western blot irreproducibility — lost reagent and parameter provenance — is closed by default.

The template is available to all ELabELN subscribers today. A new instance is live in one to two business days, and the first structured blot is typically complete within a week of account creation.

GET STARTED

Visit elabeln.com/get-started to request your ELabELN instance, or contact LabLynx at 866.522.5969 or info@lablynx.com. Load the Western Blot template, configure it for your antibody pair, and run your next blot from a tested, audit-ready baseline.

 © 2026 LabLynx, Inc. — Public information